

# ZW3520C Portable Mobile Light Tower [LED]

**LOYALS**HINE  
KEEP LOYAL, KEEP SHINE!

LED

IP  
65



## Characteristics

- 2\*100W LED lamp luminous efficiency up to 120 lm / W, can replace 2\*250W metal halide lamp, reduce energy consumption by 60%.
- Imported LED light source, seismic performance under vibration environment, life is 10 times more than traditional metal halide lamp
- 3 section adjustable telescopic gas bar, can be any lift in the 1.45m-2.8m range
- Lamps can be quickly assembled and disassembled by hand, full-cycle thermal design, long-term operating environment for high temperature and high humidity; up and down Ventilation fin structure avoid dust
- Lighting angle locking device is provided to ensure vibration environments irradiation direction is not displaced.

## Application

This product is suitable for use as large area illumination solution at the working sites of constructions, maintenance, repair, accident spot, and disaster relief etc.



## Main Specification

Item		Technical Parameters
Type		ZW3520C
Lamp	Rated voltage	220VAC
	Lamp average life	100,000h
Generator fulfill continuous working time		>6h
Lifter	Minimum height	1.45m
	The maximum rise height	2.8m
Generators	Rated capacity	12V/8.3A
	Rated output power / fuel rated capacity	900W/3.8L
Size	length × width × height	720 × 475 × 1600
Weight		47.5Kg

## Ordering Reference

Model number	Rated wattage (W)	Light output (lm)	Light distribution curve (1000cd/lm)	Equivalent to
				Metal Halide
ZW3520C-L60×2-18°	60×2	5600×2		150W×2
ZW3520C-L100×2-18°	100×2	7800×2		250W×2
ZW3520C-L60×2-60°×80°	60×2	6500×2		150W×2
ZW3520C-L100×2-60°×80°	100×2	9000×2		250W×2